

Fecha de Alta

04-07-2007

Versión

4 - 18/06/2020



**FAMILY** PREPARACIONES, FONDOS E IMPR.  
**LINE** AL USO (MASILLAS)

### DESCRIPTION AND NATURE

Extremely elastic waterproof putty. Specially formulated to treat cracks and fissures. Incorporates fibre materials which intensify its action.

### USAGES

Outdoors/Indoors

Cement

Plaster

Repair of cracks, sealing of joints, filling of holes

### PROPERTIES

- Elasticity
  - Waterproof
  - Does not decrease
- Complement for Tejamont
- No cracking at all
  - Odourless when dry
  - Good applicability

### TECHNICAL CHARACTERISTICS

|                                 |                            |
|---------------------------------|----------------------------|
| Referencia Color                | PLASMONT FIBRA ELASTICO    |
| Finish                          | Matt                       |
| Specific weight                 | 1,36± 0,05 kg/l            |
| Solids in volume                | 53± 1                      |
| Solids in weight                | 68± 1                      |
| Minimum recommended thickness   | 1 mm                       |
| Aproximated performance by coat | Depending of product usage |
| Dry to touch                    | (20°C HR: 60%, 1mm): 4-8 h |
| Dry to repaint                  | 24-48h                     |
| Colours                         | White                      |

### SURFACE PREPAIRING

#### New surfaces

Plaster and mortar cement:

-Bad condition surfaces should be anchored with Fijamont, Emulsión Fijadora or Fijalite.

-Test suitability on surface.

-Wait till complete drying of product (30 days).

-Remove off any efflorescences and neutralize alkaline surfaces.

-Extremely polished surfaces should be sandpapered to open pores.

-Remove off any foreign products or remains.

-Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply product as recommended under Application Systems and Application points.

#### Restoring and maintenance

Remove off any remains or peeling of product or any other foreign product. Open pore by sandpapering or any other mechanical systems.

Check adherence level and treat as per new surfaces.

Fecha de Alta

04-07-2007

Versión

4 - 18/06/2020

## WAY OF USE

### Application notes

- Use only recommended clean and dust-free tools as per Application Systems.
- Only repaint after indicated drying time, which depends on moisture and temperature conditions as well as coat thickness.

### Solvent for dilution and cleaning

Water

| Way of use         | Aproximate dilution |
|--------------------|---------------------|
| Large Pallette     | al uso              |
| Pallette / spatula | al uso              |

## SYSTEM

### Procedures depending of surface type

|   | Primer            | Intermedium                 | Finish  |
|---|-------------------|-----------------------------|---|
| <b>New wood/old outdoor</b>               |                   |                             |   |
| <b>MAX</b>                                |                   |                             |   |
| <b>STD</b>                                | Montopol fondo    | Plasmont Elástico           | Montoplástica, Ovaldine, Montonature, Montokril, Tejamont |
| <b>Old/New interior Wood</b>              |                   |                             |   |
| <b>MAX</b>                                |                   |                             |   |
| <b>STD</b>                                | Plasmont Elastico | Fijador (Emulsión Fijadora) | Montoplástica, Ovaldine, Montonature, Montokril, Tejamont |
| <b>Interior new/old buildings</b>         |                   |                             |   |
| <b>MAX</b>                                |                   |                             |   |
| <b>STD</b>                                | Plasmont Elastico | Fijador (Emulsión Fijadora) | Montoplástica, Ovaldine, Montonature, Montokril, Tejamont |
| <b>Outer old work painted badly state</b> |                   |                             |   |
| <b>MAX</b>                                |                   |                             |   |
| <b>STD</b>                                | Plasmont Elastico | Fijador (Emulsión Fijadora) | Montoplástica, Ovaldine, Montonature, Montokril, Tejamont |

## SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

## NOTE

Maximum recommended storage time : 36 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

Fecha de Alta

04-07-2007

Versión

4 - 18/06/2020

## PACKINGS

0.75 L, 2.5 L



## FAMILY LINE

## DESCRIPTION AND NATURE

Extremely elastic waterproof putty. Specially formulated to treat cracks and fissures. Incorporates fibre materials which intensify its action.

## USAGES

## PROPERTIES

- Elasticity
  - Waterproof
  - Does not decrease
- Complement for Tejamont
- No cracking at all
  - Odourless when dry
  - Good applicability

## TECHNICAL CHARACTERISTICS

Referencia Color

|                                 |                            |
|---------------------------------|----------------------------|
| Finish                          | Matt                       |
| Specific weight                 | 1,36± 0,05 kg/l            |
| Solids in volume                | 53± 1                      |
| Solids in weight                | 68± 1                      |
| Minimum recommended thickness   | 1 mm                       |
| Aproximated performance by coat | Depending of product usage |
| Dry to touch                    | (20°C HR: 60%, 1mm): 4-8 h |
| Dry to repaint                  | 24-48h                     |
| Colours                         | White                      |

## SURFACE PREPARING

### New surfaces

Plaster and mortar cement:

- Bad condition surfaces should be anchored with Fijamont, Emulsión Fijadora or Fijalite.
- Test suitability on surface.
- Wait till complete drying of product (30 days).
- Remove off any efflorescences and neutralize alkaline surfaces.
- Extremely polished surfaces should be sandpapered to open pores.
- Remove off any foreign products or remains.
- Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply product as recommended under Application Systems and Application points.

### Restoring and maintenance

Remove off any remains or peeling of product or any other foreign product. Open pore by sandpapering or any other mechanical systems.

Fecha de Alta

04-07-2007

Versión

4 - 18/06/2020

Check adherence level and treat as per new surfaces.

**WAY OF USE****Application notes**

-Use only recommended clean and dust-free tools as per Application Systems.

-Only repaint after indicated drying time, which depends on moisture and temperature conditions as well as coat thickness.

**Solvent for dilution and cleaning**

Water

**Way of use**

Large Pallette

Pallette / spatula

**Aproximate dilution**

al uso

al uso

**SYSTEM****Procedures depending of surface type**

|   | Primer            | Intermedium                 | Finish  |
|---|-------------------|-----------------------------|---|
| <b>New wood/old outdoor</b>               |                   |                             |   |
| <b>MAX</b>                                |                   |                             |   |
| <b>STD</b>                                | Montopol fondo    | Plasmont Elástico           | Montoplástica, Ovaldine, Montonature, Montokril, Tejamont |
| <b>Old/New interior Wood</b>              |                   |                             |   |
| <b>MAX</b>                                |                   |                             |   |
| <b>STD</b>                                | Plasmont Elastico | Fijador (Emulsión Fijadora) | Montoplástica, Ovaldine, Montonature, Montokril, Tejamont |
| <b>Interior new/old buildings</b>         |                   |                             |   |
| <b>MAX</b>                                |                   |                             |   |
| <b>STD</b>                                | Plasmont Elastico | Fijador (Emulsión Fijadora) | Montoplástica, Ovaldine, Montonature, Montokril, Tejamont |
| <b>Outer old work painted badly state</b> |                   |                             |   |
| <b>MAX</b>                                |                   |                             |   |
| <b>STD</b>                                | Plasmont Elastico | Fijador (Emulsión Fijadora) | Montoplástica, Ovaldine, Montonature, Montokril, Tejamont |

**SECURITY**

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

**NOTE**

502305


# PLASMONT FIBRA ELASTICO

Fecha de Alta

04-07-2007

Versión

4 - 18/06/2020



## PACKINGS

0.75 L, 2.5 L