

Fecha de Alta

13-04-2007

Versión

7 - 25/06/2021



FAMILY TRATAMIENTOS DE LA MADERA

LINE CATALIZADOR POLIURETANO

DESCRIPTION AND NATURE

Aromatic hardener (not yellowing) to be used with polyurethanes with white finishes, pastels and those sensitive to yellowing over time that come from the transparent Montopol Range.

USAGES

Inside

Wood

PROPERTIES

- Strongness
- Elasticity
- Resistance to the chemical attacks
- Resistance to the yellowness
- Pot life
- Formulated as hardener of white Montopol topcoat BL range

TECHNICAL CHARACTERISTICS

Referencia Color	CATALIZADOR MONTOPOL NA
Mixture relation	Ver parte A.
Finish	Transparent
Specific weight	0,92± 0,05 kg/l
Viscosity	12 +/- 2 SG
Solids in volume	21± 1
Solids in weight	26± 1
Aproximated performance by coat	Depending of product usage
Colours	Colourless

SURFACE PREPAIRING

New surfaces

New woods:

- Follow the instructions of the product range Montopol catalyze.

Restoring and maintenance

Varnished or painted wood:

- Follow the instructions of the product range Montopol catalyze.

WAY OF USE

Application notes

- Stir the product until perfectly blended.
- Mix without modifying under any circumstances the proportions of part A (Montopol Range Product), with part B (Montopol NA hardener)
- Mix with the indicated product by manually stirring with a wooden, metal or glass spatula, in a well-ventilated space, leaving it to rest for a few minutes

Solvent for dilution and cleaning

Solvent: 1410

Fecha de Alta

13-04-2007

Versión

7 - 25/06/2021

Way of use

Aproximate dilution

SYSTEM

Procedures depending of surface type

Primer

Intermedium

Finish

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 12 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

2 Kg, 10 Kg, 2.5 L, 12.5 L