

Fecha de Alta

15-02-2016

Versión

4 - 17/07/2020


FAMILY PAREDES Y TECHOS / SISTEMAS TINTOMÉTRICOS

LINE MATE PREMIUM

DESCRIPTION AND NATURE

Photocatalytic coating that purifies and purifies the interior environment, reducing gaseous pollutants and substances harmful to health (for example formaldehyde or NOx). It also works by breaking down and eliminating bad odors. Certified photocatalytic activity, it acts once the paint film dries and as long as it is kept in good condition. It also offers excellent performance as a decorative paint: smooth matt finish with high coverage and resistance.

USAGES

Indoors

Sports centres, indoor swimming pools, changing rooms, etc.

Food processing plants, supermarkets, etc

Clinics, hospitals, homes for the elderly....

Cement, Plaster, Concrete, Brick

Old, firmly fixed matt paints

Masonry

Because of its low emission and low odour properties, it is particularly recommended for indoor use.

PROPERTIES

- Reduction of organic gaseous pollutants. Up to 80% of formaldehyde removed in 3 hours (Certification as per ISO 22197:2007-4; CSIC. Instituto Torroja)
- Reduction of non-organic gaseous pollutants. NOx eliminated (ISO 22197: 2007-1; CSIC-ITQ-UPV)
- Emission free paint. Tested and classified as class A+ after 28 days of trials in WESSLING laboratories (certified to conduct trials in emission chambers).

TECHNICAL CHARACTERISTICS

Referencia Color	SMART AIRE PURO BLANCO
Finish	Matt
Specific weight	1,54± 0,05 kg/l
Viscosity	100 +/- 15 PO
Solids in volume	47± 1
Solids in weight	67± 1
VOC	Cat. a/BA 75/30 (2007/2010):0,03 g/l
Aproximated performance by coat	14-16 m ² /L
Dry to touch	(20°C HR: 60%): 1 h
Dry to repaint	(20°C HR: 60%): 3-4 h
Colours	White and a selection of colours.
Washability	Clase 2

SURFACE PREPARING
New surfaces

Cement mortars:

1. Wait until completely set (minimum 30 days)
2. Clean off any efflorescence with a sand blaster
3. Neutralise alkaline surfaces
4. Sand polished surfaces to increase porosity
5. Remove foreign products from the base
6. Fix crumbling bases with Emulsión Fijadora or Fijamont
7. Fill in any defects/flaws in the base (see family 6)

Fecha de Alta

15-02-2016

Versión

4 - 17/07/2020

Plaster:

1. Wait until the plaster is dry (maximum 20% humidity)
2. Remove undesired products from the base
3. Clean off any efflorescence with a sand blaster
4. Control the absorbency of the base using a sealant, fixative or a diluted coat of the same product.

Restoring and maintenance

1. Remove any old paint that is flaking away or in poor condition
2. Glossy surfaces should be dulled down to improve adhesion
3. On painted bases, check the existing paint is in good condition and firmly adhered, diagnose the type of paint to avoid any incompatibility, and remove dust and dirt before repainting.
4. Use plaster to fill any defects in the base (to make a suitable selection, see the PREPARING BASES family for lines corresponding to powder plaster and prepared fillers).
5. Treat mildewed surfaces with Montolimp.

WAY OF USE**Application notes**

Stir the product until perfectly blended.

Do not apply the product when room temperature is under 5°C or to surfaces exposed to strong sunlight.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	al uso
Roller	al uso
Air-less gun	5%
Air-mix gun	5%
Aerographic gun	5%
Low pressure turbo	5%

SYSTEM**Procedures depending of surface type**

	Primer	Intermedium	Finish
New work			
MAX	Smart aire puro	Smart aire puro	Smart aire puro
STD	Smart aire puro		
Old painting in good state			
MAX	Smart aire puro	Smart aire puro	Smart aire puro
STD	Smart aire puro		
Old paintings in bad state			
MAX	Eliminar+Fijador+Smart aire puro	Smart aire puro	Smart aire puro
STD	Eliminar+Smart aire puro		Smart aire puro
Plasterboard			
MAX	Smart aire puro	Smart aire puro	Smart aire puro
STD	Smart aire puro		Smart aire puro

SECURITY

Fecha de Alta

15-02-2016

Versión

4 - 17/07/2020

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adecuate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.75 L, 4 L, 12 L



FAMILY LINE

DESCRIPTION AND NATURE

Photocatalytic coating that purifies and purifies the interior environment, reducing gaseous pollutants and substances harmful to health (for example formaldehyde or NOx). It also works by breaking down and eliminating bad odors. Certified photocatalytic activity, it acts once the paint film dries and as long as it is kept in good condition. It also offers excellent performance as a decorative paint: smooth matt finish with high coverage and resistance.

USAGES

PROPERTIES

- Reduction of organic gaseous pollutants. Up to 80% of formaldehyde removed in 3 hours (Certification as per ISO 22197:2007-4; CSIC. Instituto Torroja)
- Reduction of non-organic gaseous pollutants. NOx eliminated (ISO 22197: 2007-1; CSIC-ITQ-UPV)
- Emission free paint. Tested and classified as class A+ after 28 days of trials in WESSLING laboratories (certified to conduct trials in emission chambers).

TECHNICAL CHARACTERISTICS

Referencia Color

Finish	Matt
Specific weight	1,54± 0,05 kg/l
Viscosity	100 +/- 15 PO
Solids in volume	47± 1
Solids in weight	67± 1
VOC	Cat. a/BA 75/30 (2007/2010):0,03 g/l
Aproximated performance by coat	14-16 m ² /L

Fecha de Alta

15-02-2016

Versión

4 - 17/07/2020

Dry to touch	(20°C HR: 60%): 1 h
Dry to repaint	(20°C HR: 60%): 3-4 h
Colours	White and a selection of colours.
Washability	Clase 2

SURFACE PREPAIRING

New surfaces

Cement mortars:

1. Wait until completely set (minimum 30 days)
2. Clean off any efflorescence with a sand blaster
3. Neutralise alkaline surfaces
4. Sand polished surfaces to increase porosity
5. Remove foreign products from the base
6. Fix crumbling bases with Emulsión Fijadora or Fijamont
7. Fill in any defects/flaws in the base (see family 6)

Plaster:

1. Wait until the plaster is dry (maximum 20% humidity)
2. Remove undesired products from the base
3. Clean off any efflorescence with a sand blaster
4. Control the absorbency of the base using a sealant, fixative or a diluted coat of the same product.

Restoring and maintenance

1. Remove any old paint that is flaking away or in poor condition
2. Glossy surfaces should be dulled down to improve adhesion
3. On painted bases, check the existing paint is in good condition and firmly adhered, diagnose the type of paint to avoid any incompatibility, and remove dust and dirt before repainting.
4. Use plaster to fill any defects in the base (to make a suitable selection, see the PREPARING BASES family for lines corresponding to powder plaster and prepared fillers).
5. Treat mildewed surfaces with Montolimp.

WAY OF USE

Application notes

Stir the product until perfectly blended.

Do not apply the product when room temperature is under 5°C or to surfaces exposed to strong sunlight.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	al uso
Roller	al uso
Air-less gun	5%
Air-mix gun	5%
Aerographic gun	5%
Low pressure turbo	5%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New work			
MAX	Smart aire puro	Smart aire puro	Smart aire puro
STD	Smart aire puro		


Old painting in good state

Fecha de Alta

15-02-2016

Versión

4 - 17/07/2020



MAX	Smart aire puro	Smart aire puro	Smart aire puro
STD	Smart sire puro		

Old paintings in bad state

MAX	Eliminar+Fijador+Smart aire puro	Smart aire puro	Smart aire puro
STD	Eliminar+Smart aire puro		Smart aire puro

Plasterboard

MAX	Smart aire puro	Smart aire puro	Smart aire puro
STD	Smart aire puro		Smart aire puro

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

PACKINGS

0.75 L, 4 L, 12 L