

Fecha de Alta

13-01-2011

Versión

13 - 21/04/2022


FAMILY ESMALTES / SISTEMAS TINTOMÉTRICOS

LINE MONTOMIX

DESCRIPTION AND NATURE

Acrylic water enamel of the highest quality, multi-stick for the decoration and protection of a multitude of supports: work, metal, wood, copper, galvanized, pvc,...

USAGES

Outdoors/Indoors

PVC and plastic (conduct a previous adhesion test)

Plaster

Stone

Work surfaces: cast, cement, gypsum covered brick, plasterboard

Cement mortars

Wood

Previously primed metal: iron, steel, galvanised metal, aluminium, copper, etc.

Universal use: can be combined to create the same finish on a wide range of surfaces.

Ideal for creating smooth, maximum-performance finishes on walls and ceilings. Also ideal for carpentry in general, furniture, doors, pipes, radiators, etc.

PROPERTIES


- Makes a film
- Penetration power
- Fast drying
- Security Certification for Toys according to Standard EN 71-3:2013 + A1:2014

Emission-free paint. Tested and classified as Class A+ following 28 days of testing by accredited external laboratories (certified to carry out tests in emission chambers).

- Very robust and resistant

High retention of colour and shine

- Does not turn yellow
- Euroclasses certification as per norm UNE EN 13501-1:07:B-s1-d0
- Strong resistance to the atmospheric factors

Formulated with non toxic pigment and composites

Totally washable

- No cracking at all
- Does not form blisters
- Water steam transpirable
- Odourless when dry

With anti-mould additive

Multi-adhesive

- Good applicability

TECHNICAL CHARACTERISTICS

Referencia Color	MONTONATURE MATE BLANCO
Finish	Matt
Specific weight	1,31 ± 0,05 kg/l
Viscosity	35 +/- 2 PO
Solids in volume	41 ± 1
Solids in weight	56 ± 1
VOC	Cat. d/BA 150/130 (2007/2010): 102,20 g/l

Fecha de Alta

13-01-2011

Versión

13 - 21/04/2022

Aproximated performance by coat 12-14 m²/L

Dry to touch	(20°C HR: 60%): 1 h
Dry to repaint	(20°C HR: 60%): 5-6 h
Colours	Bases: White, IN, TR White 103. Colours from the Montonature chart and tintometric system Montomix and Colora. Stained with Montotinte maximum 5%

SURFACE PREPAIRING

New surfaces

Plaster, cement and derivatives:

1. Wait until fully hardened.
2. Clear possible efflorescence from the base and neutralise alkaline surfaces. Use a suitable filler to eliminate defects in the base.
3. Treat mouldy bases with Montolimp.

New woods:

1. Apply to woods with a moisture content of less than 20%. Healthy, dry wood, well cleaned of dust and grease.
2. If the wood shows signs of ageing, it should first be sanded down, primed and any dust/powder removed through brushing or any other mechanical means.
3. Before application, prime using a suitable product, see Family 5 wood treatments.

Iron and derivatives:

1. Apply to dry bases, well cleaned of dust and grease. If these show signs of oxidation, rust must be removed through brushing or any other mechanical means. Oxifin is also suitable.
2. When this is done, treat using a suitable primer prior to application, see Family 6.

Galvanised and light metals:

- 1.- Remove all grease and check the adhesion.
- 2.- Priming with Ecoprimer is recommended where necessary.

Restoring and maintenance

Plaster, cement and painted derivatives:

1. Remove any foreign products and paint that is loose or in poor condition, opening up the grain if necessary through sanding or other mechanical means. Check the adhesion and treat as new.

Varnished or painted woods:

1. If they have been varnished or painted, remove foreign products, remove any loose or peeling varnish or paint, lightly sand, remove dust from sanding and proceed as with new woods.

Iron and enamelled derivatives:

1. On paint in good condition, sand to open the pore, check that the adhesion is perfect.
2. On paintwork in bad condition, remove by mechanical or chemical means and proceed as for new surfaces. When this is done, treat using a suitable primer prior to application, see Family 6.

Galvanised and light metals:

- 1.- Remove all grease and check the adhesion.
- 2.- Priming with Ecoprimer is recommended where necessary.

WAY OF USE

Application notes

- Stir well .
- Only apply on clean surfaces, clean off any dirt by using clean water and detergents.
- Follow guidelines as shown in table below.
- Should it be applied on specific metals, different types of galvanic or difficult surfaces, we recommend priming with Ecoprimer first.
- New wood should be previously primed with Montoxyl Fondo, to prevent surface from fungus and harmful bacteria.
- Do not apply product at high temperatures or overheated surfaces exposed to sunshine.

Fecha de Alta

13-01-2011

Versión

13 - 21/04/2022

-Keep room well ventilated while product is drying.
-Do not apply when moisture contents it over 80%.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	0-5%
Roller	0-5%
Air-less gun	5-15%
Air-mix gun	5-15%
Aerographic gun	5-15%
Low pressure turbo	5-15%

SYSTEM**Procedures depending of surface type**

	Primer	Intermedium	Finish
Galvanised and light metals			
MAX	Ecoprimer o Montoprimer Total Acqua	Montonature mate	Montonature mate
STD	Montonature mate		Montonature mate
Metal decoration			
MAX	Ecoprimer, Montoprimer Total Acqua, Montoprimer Total o Imprimación Antioxidante	Montonature mate	Montonature mate
STD	Montonature mate		Montonature mate
Old paintings in bad state			
MAX	Eliminar + Fijamont, Emulsión Fijadora	Montonature mate	Montonature mate
STD	Eliminar + Montonature mate diluido		Montonature mate
Old painting in good state			
MAX	Montonature mate		Montonature mate
STD	Montonature mate		Montonature mate
Wood			
MAX	Montoxyl fondo, Selladora Sellalux o Acqua Blanca	Montonature mate	Montonature mate
STD	Montonature mate		Montonature mate
Iron, Steel			
MAX	Montoprimer Total o Imprimación Antioxidante	Montonature mate	Montonature mate
STD	Montoprimer Total o Imprimación Antioxidante	Montonature mate	Montonature mate
Project			
MAX	Fijamont, Emulsión Fijadora	Montonature mate	Montonature mate
STD	Montonature mate diluido		Montonature mate

SECURITY

Fecha de Alta

13-01-2011

Versión

13 - 21/04/2022

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adecuate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.75 L, 4 L, 12 L



**FAMILY
LINE**

DESCRIPTION AND NATURE

Acrylic water enamel of the highest quality, multi-stick for the decoration and protection of a multitude of supports: work, metal, wood, copper, galvanized, pvc,...

USAGES

PROPERTIES




- Makes a film
- Penetration power
- Fast drying
- Security Certification for Toys according to Standard EN 71-3:2013 + A1:2014
- Emission-free paint. Tested and classified as Class A+ following 28 days of testing by accredited external laboratories (certified to carry out tests in emission chambers).
- Very robust and resistant
- High retention of colour and shine
- Does not turn yellow
- Euroclasses certification as per norm UNE EN 13501-1:07:B-s1-d0
- Strong resistance to the atmospherical factors
- Formulated with non toxic pigment and composites
- Totally washable
- No cracking at all
- Does not form blisters
- Water steam transpirable
- Odourless when dry
- With anti-mould additive

Fecha de Alta

13-01-2011

Versión

13 - 21/04/2022



Multi-adhesive

- Good applicability

TECHNICAL CHARACTERISTICS

Referencia Color

Finish	Matt
Specific weight	1,31 ± 0,05 kg/l
Viscosity	35 +/- 2 PO
Solids in volume	41 ± 1
Solids in weight	56 ± 1
VOC	Cat. d/BA 150/130 (2007/2010): 102,20 g/l
Aproximated performance by coat	12-14 m ² /L

Dry to touch	(20°C HR: 60%): 1 h
Dry to repaint	(20°C HR: 60%): 5-6 h
Colours	Bases: White, IN, TR White 103. Colours from the Montonature chart and tintometric system Montomix and Colora. Stained with Montotinte maximum 5%

SURFACE PREPARING

New surfaces

Plaster, cement and derivatives:

1. Wait until fully hardened.
2. Clear possible efflorescence from the base and neutralise alkaline surfaces. Use a suitable filler to eliminate defects in the base.
3. Treat mouldy bases with Montolimp.

New woods:

1. Apply to woods with a moisture content of less than 20%. Healthy, dry wood, well cleaned of dust and grease.
2. If the wood shows signs of ageing, it should first be sanded down, primed and any dust/powder removed through brushing or any other mechanical means.
3. Before application, prime using a suitable product, see Family 5 wood treatments.

Iron and derivatives:

1. Apply to dry bases, well cleaned of dust and grease. If these show signs of oxidation, rust must be removed through brushing or any other mechanical means. Oxifin is also suitable.
2. When this is done, treat using a suitable primer prior to application, see Family 6.

Galvanised and light metals:

- 1.- Remove all grease and check the adhesion.
- 2.- Priming with Ecoprimer is recommended where necessary.

Restoring and maintenance

Plaster, cement and painted derivatives:

1. Remove any foreign products and paint that is loose or in poor condition, opening up the grain if necessary through sanding or other mechanical means. Check the adhesion and treat as new.

Varnished or painted woods:

1. If they have been varnished or painted, remove foreign products, remove any loose or peeling varnish or paint, lightly sand, remove dust from sanding and proceed as with new woods.

Iron and enamelled derivatives:

1. On paint in good condition, sand to open the pore, check that the adhesion is perfect.
2. On paintwork in bad condition, remove by mechanical or chemical means and proceed as for new surfaces. When this is done, treat using a suitable primer prior to application, see Family 6.

Fecha de Alta

13-01-2011

Versión

13 - 21/04/2022

Galvanised and light metals:

- 1.- Remove all grease and check the adhesion.
- 2.- Priming with Ecoprimer is recommended where necessary.

WAY OF USE

Application notes

- Stir well .
- Only apply on clean surfaces, clean off any dirt by using clean water and detergents.
- Follow guidelines as shown in table below.
- Should it be applied on specific metals, different types of galvanic or difficult surfaces, we recommend priming with Ecoprimer first.
- New wood should be previously primed with Montoxyl Fondo, to prevent surface from fungus and harmful bacteria.
- Do not apply product at high temperatures or overheated surfaces exposed to sunshine.
- Keep room well ventilated while product is drying.
- Do not apply when moisture contents is over 80%.

Solvent for dilution and cleaning

Water

Way of use	Approximate dilution
Painting brush	0-5%
Roller	0-5%
Air-less gun	5-15%
Air-mix gun	5-15%
Aerographic gun	5-15%
Low pressure turbo	5-15%

SYSTEM

Procedures depending of surface type


	Primer	Intermedium	Finish
Galvanised and light metals			
MAX	Ecoprimer o Montoprimer Total Acqua	Montonature mate	Montonature mate
STD	Montonature mate		Montonature mate
Metal decoration			
MAX	Ecoprimer, Montoprimer Total Acqua, Montoprimer Total o Imprimación	Montonature mate	Montonature mate
STD	Antioxidante Montonature mate		Montonature mate
Old paintings in bad state			
MAX	Eliminar + Fijamont, Emulsión Fijadora	Montonature mate	Montonature mate
STD	Eliminar + Montonature mate diluido		Montonature mate
Old painting in good state			
MAX	Montonature mate		Montonature mate
STD	Montonature mate		Montonature mate
Wood			
MAX	Montoxyl fondo, Selladora Sellalux o Acqua Blanca	Montonature mate	Montonature mate
STD	Montonature mate		Montonature mate
Iron, Steel			

Fecha de Alta

13-01-2011

Versión

13 - 21/04/2022



MAX	Montoprimer Total o Imprimación Antioxidante	Montonature mate	Montonature mate
STD	Montoprimer Total o Imprimación Antioxidante	Montonature mate	Montonature mate

Project

MAX	Fijamont, Emulsión Fijadora	Montonature mate	Montonature mate
STD	Montonature mate diluido		Montonature mate

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

PACKINGS

0.75 L, 4 L, 12 L