

Fecha de Alta

18-04-2008

Versión

13 - 21/04/2022



FAMILY TRATAMIENTOS DE LA MADERA / SISTEMAS TINTOMÉTRICOS
LINE PROTECTORES ALCIDICOS (P. A.)

DESCRIPTION AND NATURE

Protective treatment for matt wood, for open pore finishes, in colour. Water-repellent.

USAGES

Outdoors/Indoors

Wood

Specially recommended for mountain and coastal areas

PROPERTIES

- Provides open pore finish
- Outdoor maximum protection if applied over Montoxyl Fondo Coloured
- Water resistant
- As necessary for the wood as the anti-rust products for the iron
- Strong resistance to the atmospherical factors
- No cracking at all
- Does not form blisters
- Water steam transpirable
- Odourless when dry
- Microporous
- Highlights the wood's natural grain
- U.V. resistant
- Good applicability
- Euroclasses certification as per norm UNE EN 13501-1:07:C-s1-d0

TECHNICAL CHARACTERISTICS

Referencia Color	MONTOXYL CLASSIC MATE TR
Finish	Matt
Specific weight	0,86± 0,05 kg/l
Viscosity	60 +/- 15 SG
Solids in volume	30± 1
Solids in weight	38± 1
VOC	Cat. e/BD 500/400 (2007/2010): 400,00 g/l
Aproximated performance by coat	10-16 m ² /L
Dry to touch	(20°C HR: 60%): 4-12 h
Dry to repaint	(20°C HR: 60%): 24 h
Colours	Base: TR 900 Montoxyl Chart, Pine 910, Oak 920, Walnut 930, Palisander 940, Chestnut 950, Teak 960, Mahogany 970, Ebony 980, White 990 and colours on the Cromiservice Wood chart. Montotinte unive
Classification	AFNOR: NFT. 36005 Famille I Classe 4a

SURFACE PREPAIRING

French norm DTU 59.1

Fecha de Alta

18-04-2008

Versión

13 - 21/04/2022

New surfaces

New wood:

1. The base must be free from foreign materials and/or waste matter.
2. Apply to wood with a moisture content of less than 20%.
3. Apply to wood which is healthy, dry and free from grease and dust.

Old wood

1. Sand down and remove any remnants of glue from the joints and defects from mechanical process.
2. If the wood shows signs of ageing it must first be sanded down and any dust removed using a plane or other mechanical device.
3. By using a paint gun; the most highly recommended is the Airless System.

Restoring and maintenance

Varnished or painted wood:

1. If the wood has been varnished using Montoxyl matt or satin type lasures, remove foreign materials, remove any varnish which is loose or in poor condition, gently sand down, remove the sanding dust and proceed as with new wood.
2. If the wood has been varnished using Montoxyl type flexible and penetrating protectors, remove foreign materials, remove any varnish which is loose or in poor condition, gently sand down, remove the sanding dust and proceed as with new wood.
3. If it has been varnished using a closed pore varnish like Barniz Sintético Universal Matt, Satin or Gloss, Barniz Veleró, Barniz Alta Montaña o similar, strip down with Quitamont Universal or by mechanical means and proceed as with new wood if blisters or cracks have appeared or edges are raised. If the surface is in good condition, gently sand down, remove the sanding dust and proceed as with new wood.
4. If the wood has previously been varnished with cellulose or polyurethane varnishes, strip down using Quitamont Universal (Code: 3510) or by mechanical means and proceed as with new wood.
5. If the wood has been enamelled with a synthetic enamel such as Montosintetic, Marisma, Luxatín or similar, strip down with Quitamont Universal or by mechanical means and proceed as with new wood.

WAY OF USE

Application notes

Stir the product until perfectly blended.

Apply thin, even layers.

Do not apply the product at high temperatures or on surfaces exposed to strong insolation.

Ensure good ventilation while product is drying.

Do not apply with relative moisture over 80%

Solvent for dilution and cleaning

Disolvente 1401

Way of use	Aproximate dilution
Painting brush	uso
Roller	uso
Air-less gun	uso
Air-mix gun	uso
Aerographic gun	uso
Low pressure turbo	uso
Dipping	uso

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New wood/old outdoor			
MAX	Anticarcomas Klearxyl Di	Montoxyl Classic Fondo Color	Montoxyl Classic Mate Color
STD	Anticarcomas Klearxyl Di		Montoxyl Classic Mate Color
Old/New interior Wood			
MAX	Montoxyl Classic Fondo	Montoxyl Classic Mate	Montoxyl Classic Mate Color
STD	Montoxyl Classic Fondo		Montoxyl Classic Mate

Fecha de Alta

18-04-2008

Versión

13 - 21/04/2022

varnished or painted wood

MAX	Al exterior: Decapar+ Anticarcomas Klearxyl Di	Montoxyl Classic Fondo Color	Montoxyl Classic Mate Color
STD	Al exterior: Decapar+ Anticarcomas Klearxyl Di		Montoxyl Classic Mate Color

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

2.5 L

Canned bases 0.75 L, 5 L, 10 L



**FAMILY
LINE**

DESCRIPTION AND NATURE

Protective treatment for matt wood, for open pore finishes, in colour. Water-repellent.

USAGES

PROPERTIES


- Provides open pore finish
- Outdoor maximum protection if applied over Montoxyl Fondo Coloured
- Water resistant
- As necessary for the wood as the anti-rust products for the iron
- Strong resistance to the atmospherical factors
- No cracking at all
- Does not form blisters
- Water steam transpirable
- Odourless when dry
- Microporous
- Highlights the wood's natural grain
- U.V. resistant

Fecha de Alta

18-04-2008

Versión

13 - 21/04/2022



- Good applicability
- Euroclasses certification as per norm UNE EN 13501-1:07:C-s1-d0

TECHNICAL CHARACTERISTICS

Referencia Color

Finish	Matt
Specific weight	0,86± 0,05 kg/l
Viscosity	60 +/- 15 SG
Solids in volume	30± 1
Solids in weight	38± 1
VOC	Cat. e/BD 500/400 (2007/2010): 400,00 g/l
Aproximated performance by coat	10-16 m ² /L
Dry to touch	(20°C HR: 60%): 4-12 h
Dry to repaint	(20°C HR: 60%): 24 h
Colours	Base: TR 900 Montoxyl Chart, Pine 910, Oak 920, Walnut 930, Palisander 940, Chestnut 950, Teak 960, Mahogany 970, Ebony 980, White 990 and colours on the Cromiservice Wood chart. Montotinte unive
Classification	AFNOR: NFT. 36005 Famille I Classe 4a

SURFACE PREPAIRING

French norm DTU 59.1

New surfaces

New wood:

1. The base must be free from foreign materials and/or waste matter.
2. Apply to wood with a moisture content of less than 20%.
3. Apply to wood which is healthy, dry and free from grease and dust.

Old wood

1. Sand down and remove any remnants of glue from the joints and defects from mechanical process.
2. If the wood shows signs of ageing it must first be sanded down and any dust removed using a plane or other mechanical device.
3. By using a paint gun; the most highly recommended is the Airless System.

Restoring and maintenance

Varnished or painted wood:

1. If the wood has been varnished using Montoxyl matt or satin type lasures, remove foreign materials, remove any varnish which is loose or in poor condition, gently sand down, remove the sanding dust and proceed as with new wood.
2. If the wood has been varnished using Montoxyl type flexible and penetrating protectors, remove foreign materials, remove any varnish which is loose or in poor condition, gently sand down, remove the sanding dust and proceed as with new wood.
3. If it has been varnished using a closed pore varnish like Barniz Sintético Universal Matt, Satin or Gloss, Barniz Veleró, Barniz Alta Montaña o similar, strip down with Quitamont Universal or by mechanical means and proceed as with new wood if blisters or cracks have appeared or edges are raised. If the surface is in good condition, gently sand down, remove the sanding dust and proceed as with new wood.
4. If the wood has previously been varnished with cellulose or polyurethane varnishes, strip down using Quitamont Universal (Code: 3510) or by mechanical means and proceed as with new wood.
5. If the wood has been enamelled with a synthetic enamel such as Montosintetic, Marisma, Luxatín or similar, strip down with Quitamont Universal or by mechanical means and proceed as with new wood.

WAY OF USE

Application notes

Stir the product until perfectly blended.

Apply thin, even layers.

Do not apply the product at high temperatures or on surfaces exposed to strong insolation.

Ensure good ventilation while product is drying.


Do not apply with relative moisture over 80%

Fecha de Alta

18-04-2008

Versión

13 - 21/04/2022



Solvent for dilution and cleaning

Disolvente 1401

Way of use	Aproximate dilution
Painting brush	uso
Roller	uso
Air-less gun	uso
Air-mix gun	uso
Aerographic gun	uso
Low pressure turbo	uso
Dipping	uso

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New wood/old outdoor			
MAX	Anticarcomas Klearxyl Di	Montoxyl Classic Fondo Color	Montoxyl Classic Mate Color
STD	Anticarcomas Klearxyl Di		Montoxyl Classic Mate Color
Old/New interior Wood			
MAX	Montoxyl Classic Fondo	Montoxyl Classic Mate	Montoxyl Classic Mate Color
STD	Montoxyl Classic Fondo		Montoxyl Classic Mate
varnished or painted wood			
MAX	Al exterior: Decapar+ Anticarcomas Klearxyl Di	Montoxyl Classic Fondo Color	Montoxyl Classic Mate Color
STD	Al exterior: Decapar+ Anticarcomas Klearxyl Di		Montoxyl Classic Mate Color

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

PACKINGS

2.5 L
Canned bases 0.75 L, 5 L, 10 L