

Product information | TECHNICAL DATA SHEET

CHALK BOARD PAINT

400 ml, 9.7 Oz, 275 g.

GENERAL DESCRIPTION

High opacity, matt finish, water-based paint formulated for interior decoration and transforming walls, columns or other surfaces and objects into chalkboards. It is also designed for the maintenance of chalkboards in educational centers.

FEATURES

- Fast drying.
- Odorless.
- Good adhesion.
- Excellent covering power.
- Does not contain lead nor other heavy metals.
- Easy to apply and repainting.
- Usable indoors.
- May be removed with water during the first 30 minutes of dry time. Once the paint film has hardened, it is water resistant.

APPLICATIONS

Ideal for creative works in:

- DIY
- Decoration
- Crafts

INSTRUCTIONS FOR USE

- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- For best results apply in thin layers (minimum 2 layers). Three thin layers are always better than one thick one, and may be repainted within twenty minutes with the same paint.
- After 72 hours and once the film has hardened, you may write on it with solid chalk or liquid chalk markers. To clean/erase we recommend using a damp cloth.
- Reverse the aerosol valve to purge after use, if the actuator gets blocked, replace it with a new one.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Request safety datasheets.

PHYSICAL PROPERTIES

Binder type:	PU modificado
Color:	Black matt
Brightness 60° (ASTM D-523 ISO 2813)	<15% mate
Dry to the touch (ASTM D-1640 ISO 1517):	30'
Total drying (ASTM D-1640 ISO 1517):	48-72h
Thickness of dry layer (ASTM D-823 ISO 2808):	20 µ/capa (2 coats)
Theoretical yield (continuous painting):	2,5m ² to 400 ml
Product life:	>5 years
Recoating:	After 20-30'
Ready for use:	72 h
Heat resistance of paint:	Undetermined
Condition for application:	T° environment min 8 - 35°C
	T° surface min de 10 - 40°C
	Humidity max 85% R.H.P

*Date last reviewed: 25/10/2017

APPEARANCE



LABEL



CAP SYSTEM



PACKAGING

Nominal capacity 400 ml.
Heat resistance of packaging: <50°C
Propellant: BP

Box (6 units)
205 X 140 X 200 mm.



CAUTION

